

# Safety data sheet according to 1907/2006/EC, Article 31

Version number 1

Printing date 25.06.2014

## Revision: 25.06.2014

# 1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: RIDGID HIGH PERFORMANCE THREAD CUTTING OIL
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available.
- $\cdot$  Application of the substance / the mixture Lubricant for Industrial use
- · 1.3 Details of the supplier of the safety data sheet


• Manufacturer/Supplier: RIDGE TOOL EUROPE INTERLEUVENLAAN, RESEARCH PARK HAASRODE, 3001 LEUVEN BELGIUM Tel.: +32 (0) 16380211 Fax: +32 (0) 16380210

- Further information obtainable from: Customer Service +32 (0) 16380211 (Office hours)
- **1.4 Emergency telephone number:** During normal opening times: ++49/2947/88100 Customer Service +32 (0) 16380211 (Office hours)

# 2 Hazards identification

## · 2.1 Classification of the substance or mixture

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



## R12: Extremely flammable.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

# Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

## · 2.2 Label elements

## · Labelling according to EU guidelines:

Observe the general safety regulations when handling chemicals.

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

## · Code letter and hazard designation of product:



F+ Extremely flammable

## Risk phrases:

12 Extremely flammable.

#### · Safety phrases:

- 1/2 Keep locked up and out of the reach of children.
- 16 Keep away from sources of ignition No smoking.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 51 Use only in well-ventilated areas.

according to 1907/2006/EC, Article 31

Printing date 25.06.2014

Version number 1

Revision: 25.06.2014

(Contd. of page 1)

# Trade name: RIDGID HIGH PERFORMANCE THREAD CUTTING OIL

· Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

- · Classification in accordance with Directive 75/324/EEC: Extremely flammable
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

# 3 Composition/information on ingredients

· 3.2 Chemical characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
	Zinc dialkyldithiophosphat	0.1-<0.3%
	🗙 Xi R38-41	
	₩ N R51/53	
CAS: 68476-86-8	Petroleum gases, liquefied, sweetened	25-50%
EINECS: 270-705-8	▶ F+ R12	
Index number: 649-203-00-1	Čarc. Cat. 1, Muta. Cat. 2	
Additional information: For	the wording of the listed rick phrases refer to eastion 16	

· Additional information: For the wording of the listed risk phrases refer to section 16.

# 4 First aid measures

· 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Rinse out mouth and then drink plenty of water.
- 4.2 Most important symptoms and effects, both acute and delayed Gastric or intestinal disorders
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# **5** Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- Foam
- Sand
- Carbon dioxide

CO2, sand, extinguishing powder. Do not use water.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- Additional information Cool endangered receptacles with water spray.

(Contd. on page 3)

GR -

according to 1907/2006/EC, Article 31

Printing date 25.06.2014

Version number 1

Revision: 25.06.2014

## Trade name: RIDGID HIGH PERFORMANCE THREAD CUTTING OIL

(Contd. of page 2)

# 6 Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Keep away from ignition sources. Ensure adequate ventilation Wear protective equipment. Keep unprotected persons away.
  6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
  6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents Dispose of the material collected according to regulations.
  6.4 Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

# 7 Handling and storage

#### · 7.1 Precautions for safe handling

Store in cool, dry place in tightly closed receptacles. Open and handle receptacle with care.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

#### · 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility:
- Store away from flammable substances.

Store away from oxidizing agents.

Store away from foodstuffs.

 Further information about storage conditions: Store under lock and key and out of the reach of children. Store in cool, dry conditions in well sealed receptacles. Keep container tightly sealed. Do not seal receptacle gas tight. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight.

# 8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

#### · 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

according to 1907/2006/EC, Article 31

Printing date 25.06.2014

Version number 1

Revision: 25.06.2014

(Contd. of page 3)

## Trade name: RIDGID HIGH PERFORMANCE THREAD CUTTING OIL

· 8.2 Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

# · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- Use suitable respiratory protective device in case of insufficient ventilation.
- Protection of hands: Recommendation: Chemical resistant protective gloves (EN 374)
- · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

# · Eye protection:



Tightly sealed goggles

Use safety glasses according to EN 166 : 2001.

9 Physical and chemical prope	erties
<ul> <li>9.1 Information on basic physical a</li> <li>General Information</li> <li>Appearance:</li> </ul>	and chemical properties
Form:	Aerosol
Colour:	Brown
· Odour:	Characteristic
<ul> <li>Odour threshold:</li> </ul>	Not determined.
· pH-value:	Not determined.
<ul> <li>Change in condition</li> <li>Melting point/Melting range:</li> <li>Boiling point/Boiling range:</li> </ul>	Undetermined. -44 ℃
· Flash point:	-60 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	287 ℃
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
· Explosion limits:	
Lower:	0.9 Vol %
Upper:	9.5 Vol %
· Vapour pressure at 20 °C:	0.1 hPa
	(Contd. on page 5)

according to 1907/2006/EC, Article 31

Printing date 25.06.2014

Version number 1

Revision: 25.06.2014

## Trade name: RIDGID HIGH PERFORMANCE THREAD CUTTING OIL

		(Contd. of page 4)
· Density at 20 °C:	0.5 g/cm <sup>3</sup>	
· Relative density	Not determined.	
· Vapour density	Not determined.	
<ul> <li>Evaporation rate</li> </ul>	Not applicable.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wat	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	0.0 %	
· 9.2 Other information	No further relevant information available.	

# 10 Stability and reactivity

- · 10.1 Reactivity Reacts with strong oxidants and strong reducing agents under severe heat.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid Temperatures above 50 °C can result in breakage of the container
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

Emergence of flammable gases / vapors on contact with strong oxidizing agent' s possible.

# 11 Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

# · LD/LC50 values relevant for classification:

#### Zinc dialkyldithiophosphat

Oral LD50 >15000 mg/kg (rat)

Dermal LD50 4100 mg/kg (rabbit)

## Primary irritant effect:

- on the skin: May cause skin irritation after repeated contact.
- on the eye: May cause slight irritation to the eyes.
- Sensitization: No sensitizing effects known.

# 12 Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 6)

according to 1907/2006/EC, Article 31

Printing date 25.06.2014

Version number 1

Revision: 25.06.2014

# Trade name: RIDGID HIGH PERFORMANCE THREAD CUTTING OIL

(Contd. of page 5)

## 12.5 Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

# 13 Disposal considerations

- 13.1 Waste treatment methods
   Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

Transport information	
14.1 UN-Number ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR IMDG IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
Class	2.1
Label	2.1
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Danger code (Kemler):	Warning: Gases.
EMS Number:	- F-D,S-U
14.7 Transport in bulk according to Ann MARPOL73/78 and the IBC Code	ex II of Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Transport category	1L 2
	(Contd. on p

according to 1907/2006/EC, Article 31

Printing date 25.06.2014

Version number 1

Revision: 25.06.2014

## Trade name: RIDGID HIGH PERFORMANCE THREAD CUTTING OIL

(Contd. of page 6)

Tunnel restriction code

D

# 15 Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

### · Labelling according to EU guidelines:

Observe the general safety regulations when handling chemicals.

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

#### · Code letter and hazard designation of product:



F+ Extremely flammable

#### · Risk phrases:

12 Extremely flammable.

#### · Safety phrases:

- 1/2 Keep locked up and out of the reach of children.
- 16 Keep away from sources of ignition No smoking.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 51 Use only in well-ventilated areas.

#### · Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

- · Classification in accordance with Directive 75/324/EEC: Extremely flammable
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

- R12 Extremely flammable.
- R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Department issuing MSDS: Customer Service +32 (0) 16380211 (Office hours)

GB —