



Clow Reach-A-Light Ladder

With 5 different variations, the Clow Reach-A-Light ladder is the ultimate in versatility and is ideal for those difficult to reach jobs.

Configurations include a Step Ladder, an Extended Step Ladder, a Single Section Ladder, a Double Section Ladder and Triple Section Ladder.

Ideal for use in church halls, gymnasiums and any buildings with similarly high ceilings where a free standing and self supporting ladder is required.

Unique automatic rung locks prevent the ladder sections accidentally separating when the ladder is in use.

Suitable for use by the professional or DIY enthusiast.

- Easily transported
- Box-section aluminium stiles
- Automatic rung locks
- Non-slip aluminium treads
- Light weight
- Robust & durable
- EN131: Professional Standard
- Maximum load 150kg



Clow Reach-A-Light Ladder	CRL1	CRL2	CRL3
Number of Rungs	3 x 7	3 x 9	3 x 11
Maximum Ladder Length	4.40m	6.08m	7.76m
Closed Length	2.16m	2.72m	3.28m
Height as an "A" Frame Ladder	2.03m	2.56m	3.08m
Height as a "Freestanding" Ladder	3.08m	4.13m	5.19m
Stabiliser Width	0.90m	1.2m	1.35m
Weight	13.0kg	19.0kg	24.0kg