



# We call it 'Non-Powered, Powered Access'

As part of the Eco range the EcoLift still harnesses the same Eco friendly revolutionary 'Patented Stored Power System' as the PecoLift but at 4.20 m offers almost a metre extra in working height.

With no batteries (to charge and look after) and no hydraulic oil, the EcoLift is truly an Eco friendly solution.

## Typical applications and uses:

1st & 2nd Fix. Pipe Work, M & E. FM. Cleaning. Painting. Retail. Point of Sale. FM.

### **Key Features**

- Intuitive to operate turn handle to elevate
- Patented\* lift mechanism, no power required
- Lightweight, easy to manoeuvre
- Small foot print (1.28 m x 0.70 m)
- Unlimited lift cycles, can be used 24/7
- Robust design for years of trouble free service
- Minimal operational costs, virtually maintenance free

# PUSH AROUND - Self Powered Indoor Use

Working Height: 4.20 m

**Applications:** 1st & 2nd fix. Pipe Work, M&E. F.M. Cleaning. Painting. Point of Sale. Retail.





4.20 m

2.20 m

200N

234 kg

0 degrees

0.85 m (L) x 0.64 m (W)

150 kg (1 person + tools)

Internal use only 0 m/s

1.28 m x 0.70 m

234 kg (2.29kN)

less then 70Dba

#### Specifications

#### WORKING DIMENSIONS

Maximum working height: Maximum platform height: Basket dimensions: Working foot print: Safe working load - platform: Maximum manual force: Maximum gradient for operation: Maximum wind force: Maximum castor point load: Maximum wheel force: Power Sound Level:

#### **CLOSED DIMENSIONS**

Length: 1.28 m Width: 0.70 m Height: 1.94 m Weight: 305 kg

LIFT CYCLES Unlimited

#### **Safety features**

- 'Auto-lok' brake on elevation
- Elevates only when operated
- Lifting mechanism interlocked





#### **IMPORTANT**

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.

#### **JLG EMEA BV**

Polaris Avenue 63 2132 JH Hoofddorp The Netherlands Phone: +31 (0)23 565 5665 www.jlg.com

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.

An Oshkosh Corporation Company