

## We call it 'Non-Powered, Powered Access'

Battery and electric power free, the PecoLift is elevated by simply and easily rotating the handle; the patented lift mechanism glides you smoothly to your chosen working height in seconds.

With no batteries (to charge and look after) and no hydraulic oil the PecoLift is truly an Eco friendly solution. It's tiny footprint and simplicity of use finally provides a purely mechanical solution that doesn't involve erecting, unfolding or climbing.

### Key Features

- Intuitive to operate - turn handle to elevate
- Patented\* lift mechanism, no power required
- Lightweight, easy to manoeuvre
- Small foot print (0.99 m x 0.70 m)
- Unlimited lift cycles, can be used 24/7
- Robust design for years of trouble free service
- Minimal operational costs, virtually maintenance free

### **PUSH AROUND - Self Powered**

Indoor Use

**Working Height:** 3.50 m

**Applications:** Pipe Work,  
M&E. Cleaning. Painting.  
Retail. FM.



# Model PECOLIFT

LOW-LEVEL ACCESS

## Specifications

### WORKING DIMENSIONS

Maximum working height:	3.50 m
Maximum platform height:	1.50 m
Basket dimensions:	0.72 m (L) x 0.60 m (W)
Working footprint:	0.99 m x 0.70 m
Safe working load:	150 kg (1 person + tools)
Maximum manual force:	200N
Maximum gradient for operation:	0 degrees
Maximum wind force:	Internal use only 0 m/s
Maximum castor point load:	125 kg (1.23kN)
Maximum wheel force:	125 kg
Power Sound Level:	less than 70DbA

### CLOSED DIMENSIONS

Length:	0.99 m
Width:	0.70 m
Height:	1.55 m
Weight:	180 kg

**LIFT CYCLES** Unlimited

## Safety features

- Auto-braked on entering basket
- 'Auto-lok' brake on elevation
- Elevates only when operated
- Lifting mechanism interlocked



## IMPORTANT

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.

## JLG EMEA BV

Polaris Avenue 63  
2132 JH Hoofddorp  
The Netherlands  
Phone: +31 (0)23 565 5665  
[www.jlg.com](http://www.jlg.com)

An Oshkosh Corporation Company