

Product information

61cc 12" Disc Cutter



Satisfying the professional's needs

EK6100

Max. Cutting Depth	110 mm
Noise sound pressure	100 dB(A)
Noise sound power	109 dB(A)
Engine	2-Stroke
Arbor	20 mm
Max Wheel Speed	5,100 rpm
Wheel diameter	305 mm
Power Rating	4.2 hp
Fuel Tank Capacity	0.7 litres
Fuel Type	Mixed Gasoline
Displacement	61 cm ³
Power Rating	3.2 kW
Vibration: Right Handle (Rear grip)	3.6 m/sec ²



STANDARD EQUIPMENT: B-13281 DIAMAK+ SEGMENTED RIM, B-13297 DIAMAK+ SEGMENTED RIM, B-13306 DIAMAK+ Segmented rim, B-13312 DIAMAK+ SEGMENTED RIM, B-13459 QUASAR SEGMENTED RIM

- Rapid start pull force required to start the machine is drastically reduced with spring-assisted recoil starter.
- Touch and Stop Switch
- Fuel primer for easy starting.
- High quality driving belt does not require tensioning once the proper tension is adjusted.
- Enhanced Air Filtration
- Developed in compliance with all known exhaust emission regulations
- Lightweight; 1.2kg (2.6lbs) lighter than DPC6430
- Water supply with intake filter and fine adjustment for adequate dust protection.

Details correct as of: 5-5-2015

Makita reserve the right to change specifications at any time owing to their policy of constant improvement.

Accessories shown are not necessarily supplied.

www.makita.com