



BROUGHTON PLANT HIRE & SALES

Unit 10, Trade City, Ashton Road, Romford, Essex RM3 8UJ
 TELEPHONE: 01708 383350 FAX: 01708 383359

www.broughtonplanthire.co.uk

Clow EN131: Professional Superglas® AR Platform Step

The all new Clow Superglas® AR Step is a sturdy, durable "All Round" platform step offering safe 360° access from a strong supporting platform.

Wide integrated handrails, a wrap a round rear guardrail and gravity locking front guardrail means this step provides operatives with a safe and secure non-slip access platform ideal for wide range of tasks.

Insulated GRP stiles, rigid back bars, reinforced non-slip treads together with parallel steel locking stays and transport wheels make this step robust and manoeuvrable.

Available ex-stock in 2, 3, 4, 5, 6, 7 and 8 tread sizes, these steps are supplied flat packed and complete with all required assembly tools.

Conforming with with European Standard EN131: Professional the Superglas® AR Platform Step safely supports a 150kg load.



Code	Treads	Weight	Height to Platform	Platform Dimensions	Open Height
FPS2	2 Tread	12.2kg	560mm	400mm x 580mm	1510mm
FPS3	3 Tread	13.8kg	850mm	400mm x 580mm	1790mm
FPS4	4 Tread	15.1kg	1150mm	400mm x 580mm	2054mm
FPS5	5 Tread	16.2kg	1450mm	400mm x 580mm	2335mm
FPS6	6 Tread	18.0kg	1750mm	400mm x 580mm	2612mm
FPS7	7 Tread	19.0kg	2050mm	400mm x 580mm	2896mm
FPS8	8 Tread	20.7kg	2350mm	400mm x 580mm	3170mm