




Comfort-Line Pressing Unit ECO301

Ideal for press joints
up to 108 mm

- Short pressing cycles ensure quick and economic work process
- Process-based monitoring of the complete pressing cycles
- Electronic jaw-locking-bolt
- Signal tone confirms fully executed pressings

 Metal up to 108 mm

 Compact tool dimensions

 Automatic return

 Robust design



Press jaws and
press collars

An optimal tool-system

ECO301 is a perfect combination of pressing unit, press jaw and press collar resulting in an optimal tool-system. The electronic monitoring of the pressing process is an important advantage in use.

This method requires low pressing energy and offers an optimum of force-dispersion for reliable pressing results.

Scope of application

- Drinking water-, gas- and heating installations, industry and commercial applications and many more
- Availability of jaws suitable for M-Profile fittings of various manufacturers in the market*

Accessories

- Press jaws PB3
- Press collars with adaptor jaw ZB303 / ZB323 / ZB324
- Available for many worldwide common power supplies



An easy replacement of the press collars and jaws is ensured.

Novopress quality and service

Comfort-Line

- Error display
- Device information through the LED indication under the start button
- Automatic pressing cycle

Maintenance and service

- Qualified service on site thanks to international service network
- Mobile on-site service thanks to our service vehicle in Germany and parts of Europe
- Extended warranty (further information at www.novopress.de)



Technical Data ECO301

Dimensions:	Metal pipe up to 108 mm
Weight:	5.0 kg
Length:	420 mm
Width:	85 mm
Height:	110 mm
Power consumption:	560 W
Piston force:	max. 45 kN
Piston stroke:	45 mm

* for binding information please request your system manufacturer