

ESG 105 Battery powered hydraulic cutting tool 105 mm dia.







- ▶ Cuts copper and aluminium cables with armouring
- ▶ 120 kN cutting force for extremely wide cutting range up to 105 mm dia.
- ▶ Remarkably lightweight for tools in this performance class
- ▶ Saves time with multiple cuts thanks to innovative opening mechanism
- All tool data in view thanks to display and i-press® app

Characteristics

- Choose your battery system: Bosch or Makita
- All data can be easily read via Bluetooth
- Closed head with bolt interlock, rotatable, flip top style
- Simple and safe: One-button operating concept for controlling all tool functions
- Effortless working due to balanced centre of gravity
- LED for work area illumination
- 2-stage hydraulic system with fast feed and power stroke
- Simple and safe: Automatic retraction when operation is complete
- Manual retract stop (MRS) for efficient operations
- Always ready-to-use thanks to battery charge and service display

Suitable for

lightly armoured Cu and Al cables

Makita battery 18 V / 4.0 Ah, Li-lon

Guillotine closed			
max. 105 mm dia.			
120 kN			
Depending on cable type			
45 min.			
10.7 kg			
-10 °C up to +40 °C			
	Part No. Bosch	Part No. Makita	
g tool 105 mm dia.	ESG105CFB	ESG105CFM	
			Page
on	RALB2EU		493
lon battery	LGLB1EU		494
-lon battery		RAL40	492
n		LGL1	494
on	MK105NG	MK105NG	
			Page
	ESG105ES		
	ESG105EF		
on	RALB2EU		493
	max. 105 mm dia. 120 kN Depending on cable typ 45 min. 10.7 kg -10 °C up to +40 °C g tool 105 mm dia. on lon battery lon battery n	max. 105 mm dia. 120 kN Depending on cable type 45 min. 10.7 kg -10 °C up to +40 °C Part No. Bosch ESG105CFB on RALB2EU Ion battery LGLB1EU -lon battery n MK105NG ESG1 ESG1	max. 105 mm dia. 120 kN Depending on cable type 45 min. 10.7 kg -10 °C up to +40 °C Part No. Bosch g tool 105 mm dia. ESG105CFB ESG105CFM RALB2EU Ion battery LGLB1EU -lon battery RAL40 m LGL1 on MK105NG MK105NG ESG105EF

RAL40

492